

PRVPATENT- OCH REGISTRERINGSVERKET
Patentavdelningen**Intyg
Certificate**

Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.



(71) Sökande Mamea Imaging AB, Stockholm SE
Applicant (s)

(21) Patentansökningsnummer 0300808-3
Patent application number

(86) Ingivningsdatum 2003-03-21
Date of filing

REC'D	14 APR 2004
WIPO	PCT

Stockholm, 2004-03-24

För Patent- och registreringsverket
For the Patent- and Registration Office

Marita Öun
Marita Öun

Avgift
Fee

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

BEST AVAILABLE COPY

BEST AVAILABLE COPY

P16744SE.A01, BA, 2003-03-21

Ink. t. Patent- och reg.ver

2003-03-21

Huvudfaxen Kass

Title

A REFRACTIVE X-RAY ELEMENT

5

Technical field of the invention

The present invention relates to a refractive element suitable for refracting x-ray beams of the type that comprises a material having sections removed. The invention also relates to a lens comprising the refractive elements.

10

Background of the invention

99 02 29 16 WO 0112345, by the same inventor and same applicant, relates to a refractive arrangement for X-rays, and specially to a lens comprising: a member of low-Z material. The low-Z material has a first end adapted to receive x-rays emitted from an x-ray source and a second end from which the x-rays received at the first end emerge. It further comprises a plurality of substantially triangular formed grooves disposed between the first and second ends. The plurality of grooves are oriented such that, the x-rays which are received at the first end, pass through the member of low-Z material and the plurality of grooves, and emerge from the second end, are refracted to a focal line.

20

The aperture of a Multi-Prism Lens (MPL) or a.k.a. saw-tooth refractive lens, is limited by absorption of the beam in the lens material. The intensity transmission function of the lens is Gaussian with a root-mean-square (rms) width given by

25
$$\sigma_{abs} = \sqrt{F\delta}, \quad (1),$$

where F is the focal length, δ is the decrement of the real part of the index of refraction, and l is the attenuation length. The aperture in turn limits the possible intensity gain and diffraction-limited resolution. Apart from the focal length, the aperture is only a function of the material properties, and is thus a true physical limit. Choosing a material with lowest possible atomic number maximizes it. Until now, various polymers, diamond, beryllium, silicon and lithium have been used as lens materials. The choice of material is

30

of course also restricted by available fabrication methods and is furthermore a cost issue.

5 The focusing power of a lens is a function of the phase-shift of the outgoing wave. If a cylindrical wave (= phase-shift) is created, the wave will converge to a line focus. In a regular MPL, for a large portion of the lens aperture, the wave is phase-shifted much more than 2π (or 360°). In other words, rays will pass a thickness of material larger than the 2π -shift length, given by

$$L_{2\pi} = \lambda / \delta \quad (2).$$

10 This length is of the order of 10-100 μm for hard x-rays. λ is the wavelength.

Short description of the invention

The main object of the preferred embodiment of the present invention is to overcome the above-mentioned limitation.

15

Thus, the absorption of the MPL is reduced. The lens aperture and intensity gain are increased substantially, and also diffraction-limited resolution is improved. This will leave the phase of the wave unchanged and does not alter the focusing properties.

20 For these reasons, a refractive X-ray element is provided according to the preferred embodiments of the present invention. The refractive element, suitable for refracting x-rays, comprising a body of low-Z material having a first end adapted to receive rays emitted from a ray source and a second end from which the rays received at the first end emerge. The refractive element comprises columns of stacked substantially identical
25 prisms. The prisms are produced by removal of material corresponding to a multiple of a phase-shift length (L_{2n}) of a multiple of $2n$. Preferably, an intensity transmission of the element is

$$T(y) = \exp(-X(y)/l) = \exp(-k|y|l)$$

wherein $X(y)$ is the total path length for a ray through the element, I is an attenuation length, k is constant and y is the distance to the optical axis. The effective aperture is defined by:

$$D = \frac{8\delta^2 IF}{\lambda \tan \theta}$$

5 wherein F is the focal length, δ is the decrement of a real part of an index of refraction, I is an attenuation length and θ is the side angle of the prisms. The aperture increase factor (AIF) is defined by:

$$AIF = 3.2 \cdot \frac{\sigma_{\text{rms}}}{L_{2\pi} \tan \theta}$$

10 wherein σ_{rms} is root-mean-square width of MPL aperture, $L_{2\pi}$ is 2π -shift length, and θ is the side angle of the prisms.

Most preferably, the element comprises of one or several of Silicon or diamond.

15 According to the preferred embodiment, a focal length is controlled by a deviation length (y_0) of one end of the element with respect to the incident ray.

20 The invention also relates to a lens, suitable for x-rays, comprising a body with low-Z material having a first end adapted to receive rays emitted from a ray source and a second end from which the rays received at the first end are refracted. The lens comprises two columns of stacked substantially identical prisms arranged in an angle relative each other. The prisms are produced by removal of material corresponding to a multiple of a phase-shift length ($L_{2\pi}$) of a multiple of 2π . The columns are displaced relative each other. In one embodiment said columns are rotated relative each other. The columns may be arranged in series.

25

The invention also relates to an x-ray apparatus comprising at least an x-ray source and a detector assembly, further comprising a refractive element having above-mentioned features.

The invention also relates to an x-ray apparatus comprising at least an x-ray source and a detector assembly, further comprising a lens having above-mentioned features.

- 5 The invention also provides for a method for fabricating an element having above-mentioned features, the method comprising: providing an element comprising prism-patterns by lithographic patterning and subsequent deep-etching in silicon. The method further comprises using the element as moulds for chemical vapor deposition of diamond.

10

The invention also provides for a method for reducing absorption in multi-prism lens, the method comprising removing material only resulting in a phase-shift of a multiple of 2π .

Short description of the drawings

- 15 In the following, the present invention will be described in a non-limiting way with reference to enclosed drawings, in which:

Fig. 1 is a schematic cross-sectional view of a loose geometry of an element, according to one embodiment of the invention,

- 20 Fig. 2 is a schematic side view of the compact geometry of a refractive element, according to one preferred embodiment of the invention,

Fig. 3 is a schematic side view of lens element according to one preferred embodiment of the invention,

Fig. 4 is a diagram illustrating a lens transmission, according to one exemplary embodiment of the invention,

- 25 Fig. 5 is a diagram illustrating another lens transmission, according to one exemplary embodiment of the invention,

Figs. 6a and 6b illustrate a special case of MPL with minimized absorption,

Fig. 7 is a diagram illustrating transmission and averaged transmission as a function of physical lens aperture in a special case of the invention,

Fig. 8 is a very schematic frontal view of an x-ray apparatus employing a lens according to the present inventions, and

Fig. 9 is a very schematic perspective view of two serially arranged refractive elements, according to one embodiment of the present invention.

5

Detailed description of the preferred embodiments

The basic idea is to remove material corresponding to a multiple of $L_{2\pi}$, preferably made of a low-Z material. Thus, the absorption of the MPL is reduced by removing material only resulting in a phase-shift of a multiple of 2π . However, absorption can be
10 substantially reduced and thus the aperture increased. This is analogous to the concept of Fresnel lenses. Notice, however, that the proposed lens will still be comprised of structures with only flat surfaces. Also, the focal length can still be changed mechanically, by varying the angle between the lens and the beam direction (α).

15 Consider first the following structure, in which a channel 11 is made through a prism 10 with a width of the 2π -shift length (b), as illustrated schematically in Fig. 1a. Subsequent channels 11b with widths of multiple 2π -shift lengths ($m.b$) can be made, until the lens has a staircase profile on the inside.

20 A better way would be to compact a hollow prism 20 into a column of identical small prisms 21, illustrated in Fig. 2, which shows a preferred embodiment of a refractive element according to the first aspect of the invention.

25 A lens 30 according to a second aspect of the invention is illustrated in Fig. 3. The lens comprises two refractive elements 20, as illustrated in Fig. 2. The lens is formed by arranging the refractive elements edge-to-edge in one end and edges spaced apart at the other end, thus forming a substantially triangle-shaped lens. Rays 35a incident at one gable, i.e. the edge-to-edge end of the elements, are refracted and focused rays 35b at the spaced apart edge. Preferably, the focal length is controlled by y_0 .

30

Following definitions and geometrical relations are valid concerning the element 20 in Fig. 2:

$$\tan \theta = \frac{2h}{b}, \quad y_0 = M \cdot h, \quad L = N \cdot b, \quad \alpha = \frac{y_1}{L}$$

(3)

wherein θ is the angel between a triangle shaped prism sides, h is the height of a triangle shaped prism, b is the base width of a triangle shaped prism, y_0 is the inclination height of the column, y_1 is the column height, M is the number of the prisms in height direction, L is the length of the column, N is the number of the prisms in the length direction and α is the inclination angle of the columns.

Calculation of projected lens profile

The phase condition is

$$b = nL_{2\pi} = n\lambda / \delta,$$

(4)

where n is an integer; In the following it is assumed that $n=1$, δ is the decrement of the real part of the index of refraction and λ is the wavelength.

The thickness of the material in the first column at a lateral position y is:

$$x(y) = \text{mod}(2y / \tan \theta, b),$$

(5)

where $\text{mod}()$ is the remainder after division.

The next column will be displaced a distance $\delta y = b\alpha$ (α can be small), and in the i th column (starting at 0) the displacement is $i \cdot \delta y$. An incoming ray, parallel with the optical axis, will go through a thickness of material in the i th column given by

$$x_i(y) = x(y - i \cdot \delta y) = \text{mod}\left(\frac{2(y - i \cdot \delta y)}{\tan \theta}, b\right)$$

(6),

and the total path length is

$$X(y) = \sum_{i=0}^{\text{div}(y, \delta y)} x_i(y) = \sum_{i=0}^{\text{div}(y, \delta y)} \text{mod}\left(\frac{2(y - i \cdot \delta y)}{\tan \theta}, b\right)$$

(7).

Let us write $y = (j+t)\delta y$, where j is an Integer and $0 \leq t < 1$.

$$X(y) = \sum_{i=0}^j \text{mod} \left(\frac{2\delta y}{\tan \theta} (j+i-i), b \right) \quad (8)$$

$$X(j, i) = \sum_{i=0}^j \left[\frac{2\delta y}{\tan \theta} (i+i) - b \cdot \text{div} \left(\frac{2\delta y}{\tan \theta} (i+i, b) \right) \right] \quad (9)$$

$$X(j, i) = \frac{\delta y}{\tan \theta} [j(j+1) + 2(j+1)i] - b \sum_{i=0}^j \text{div} \left(\frac{2\delta y}{\tan \theta} (i+i, b) \right) \quad (10)$$

5 Small-scale variation

The first term is the well-known term for a multi-prism lens. The deviation from a parabola with apex in $y = -\delta y/2$ is

$$\Delta X(j, i) = \frac{\delta y}{\tan \theta} [(j+i+1/2)^2 - j(j+1) - 2(j+1)i] = \frac{\delta y}{\tan \theta} [1/4 + i(i-1)] \quad (11)$$

10 The constant phase-shift can be neglected and calculate the rms-deviation over the segment,

$$\langle \Delta X(i) \rangle_i = \frac{\delta y}{\tan \theta} \left(\int_0^1 i^2 (i-1)^2 di \right)^{1/2} = \frac{\delta y}{\sqrt{30} \cdot \tan \theta} = L_{2s} \frac{\alpha}{\sqrt{30} \cdot \tan \theta} \ll L_{2s} \quad (12)$$

for all reasonable values. The parabolic approximation yields

$$X_0(j) = \frac{\delta y}{\tan \theta} j^2 = \frac{y^2}{\delta y \tan \theta} = \frac{y^2}{2R}, \quad (13)$$

and the focal length is:

$$15 \quad F = \frac{R}{\delta} = \frac{\delta y \tan \theta}{2\delta} = \frac{b \alpha \tan \theta}{2\delta} = \frac{\lambda \alpha \tan \theta}{2\delta^2}, \quad (14)$$

Since the second term of equation (10) cannot change the phase of the wave (other than $\pm m \cdot 2\pi$), it will not have any influence on the focusing.

Large-scale profile

20 Studying the term by introducing γ through $b = \gamma \cdot 2\delta y / \tan \theta$.

$$X'(j, r) = b \sum_{i=0}^j \text{div}(i+r, \gamma) = b \sum_{i=0}^j \text{div}(i, \gamma) = \frac{\delta \gamma}{\tan \theta} (j^2 + j - \gamma).$$

The result is:

$$X(y) = X_0(y) - X'(y) = \frac{\delta \gamma}{\tan \theta} j \gamma = \frac{b \tan \theta}{4 \delta F} \cdot y. \quad (16)$$

5

and since $b = L_{2n} = \lambda \sqrt{\delta}$.

$$X(y) = \frac{\lambda \tan \theta}{4 \delta^2 F} \cdot y = k \cdot y \quad (17)$$

γ should be replaced by $\gamma-1$ for integers. In most situations, however, γ is relatively large
10 in which case a small error can be obtained.

Transmission and gain

The intensity transmission is

$$T(y) = \exp(-X(y)/l) = \exp(-k|y|l) \quad (18)$$

15

and the effective aperture

$$D = \int_{-\infty}^{\infty} \exp(-k|y|l) dy = \frac{2l}{k} = \frac{8 \delta^2 l F}{\lambda \tan \theta}. \quad (19)$$

For the multi-prism lens we have

$$20 \quad D_{MPL} = \sqrt{2\pi} \sigma_{abs} = \sqrt{2\pi} \cdot \sqrt{\delta F}. \quad (20)$$

The aperture increase factor (AIF) is

$$AIF = \frac{D}{D_{MPL}} = 3.2 \cdot \frac{\delta^{3/2} \sqrt{l F}}{\lambda \tan \theta}. \quad (21)$$

25 or, perhaps better expressed,

$$AIF = 3.2 \cdot \frac{\sigma_{abs}}{L_{2\pi} \tan \theta}$$

Using a material such as diamond, for example, will at 20 keV with $F=0.2$ m give $AIF = 4.5/\tan \theta$.

5

There is a dependency between the material and energy:

- Assuming low energy, so that Compton scattering can be neglected:

$$D \propto \frac{\delta^2 I}{\lambda} \propto \frac{\rho^2 E^{-4} \rho^{-1} Z^{-3.2} E^3}{E^{-1}} = \frac{\rho}{Z^{3.2}} \quad (23)$$

10

- Assuming high energy, so that photo-absorption can be neglected:

$$D \propto \frac{\delta^2 I}{\lambda} = \frac{\rho^2 E^{-4} \rho^{-1}}{E^{-1}} = \frac{\rho}{E^3} \quad (24)$$

wherein ρ is density and Z = atomic number.

Thus, it is evident that by interesting results:

15

- The material density plays a role, which it does not for the MPL.
- The dependence on atomic number is stronger than for the MPL.
- There is no optimal energy. The aperture (gain) reaches a plateau for low energies.

These factors combined make diamond 15 times better than for example Silicon (Si) at 20 keV. For the MPL the ratio will be less than 3.

20

Fig. 4 illustrates lens transmissions for a lens with reduced absorption and a normal MPL for comparison. Si is used as lens material, with $F=83$ cm at 40 keV. From left to right in the diagrams $\tan \theta$ varies with 0.2, 0.5 and 1 giving AIFs 5.1, 2.5 and 1.4, respectively.

25

Fig. 5 illustrates Lens transmission for a lens with reduced absorption and a normal MPL for comparison. Lens is made of diamond with $F=27$ cm at 20 keV. From left to right in

the diagrams $\tan \theta$ varies with 0.2, 0.5 and 1 giving AIFs 11.3, 7.9 and 5.0, respectively.

2003-03-2

Huvudfaxen Ki

In the following a special case is investigated with $\gamma=1$. This means that adjacent columns are shifted exactly one prism, giving $X(y)_{\gamma=0} = 0$. See illustrated lens in Figs. 6a and 6b. Fig. 6a illustrates a real lens and Fig. 6b the ray projection profile.

From the expression derived above, it is found:

$$\langle \delta X(r) \rangle = L_{xx} \frac{\alpha}{\sqrt{30} \cdot \tan \theta} = \frac{L_{xx}}{2\sqrt{30}} \quad (25)$$

10

The rms phase error is $\sigma_\phi = \pi/\sqrt{30}$ and the Intensity reduction factor (IRF) is

$$\text{IRF} = \exp(-\sigma_\phi^2) = \exp(-\pi^2/30) = 0.72. \quad (26)$$

Thus, the Intensity is reduced by 28% compared to a perfect parabolic lens.

15

Using $2\alpha = \tan \theta$ gives

$$F = \frac{b\alpha \tan \theta}{2\delta} = \frac{L_{xx} \tan^2 \theta}{4\delta} = \frac{\lambda \tan^2 \theta}{4\delta^2} \quad (27)$$

In this energy regime, it is a rather good approximation to take

$$\delta = 2 \cdot 10^{-4} \rho E^{-2} \quad (28)$$

20

if ρ and E are expressed in g/cm^3 and keV, respectively. Using $\lambda = 12.4 \text{ \AA}/E$, the result is:

$$F = \frac{12.4 \cdot 10^{-10} \tan^2 \theta}{4 \cdot 4 \cdot 10^{-8} \rho^2 E^{-2}} \text{ m} = 7.7 \text{ mm} \cdot \frac{E^2 \tan^2 \theta}{\rho^2} \quad (29)$$

For a diamond, for example, at 15 keV, $F = 2.1 \text{ m} \cdot \tan^2 \theta$, and if $\tan \theta = 1/4$ then $F = 13 \text{ cm}$. Thus, targeted focal lengths can be reached with reasonable values of θ .

25

For this special case, the profile can be given as

$$X(j, t) = t(j+1)L_{2n}. \quad (30)$$

5 and the transmission

$$T(j, t) = \exp(-t(j+1)L_{2n}/l). \quad (31)$$

Averaging over t gives

$$T(j) = \frac{l[1 - \exp(-(j+1)L_{2n}/l)]}{(j+1)L_{2n}}. \quad (32)$$

10

Summing over the lens aperture gives the effective aperture

$$D = \delta y \sum_{j=1}^{\infty} T(j) = \infty. \quad (33)$$

15 Consequently, a lens with "infinite" aperture is provided. This is of little practical importance though, since the sum increases very slowly for large j 's.

Let us change variables through $j=q \cdot l/L_{2n}$. It is a good approximation to take

$$D(q) = \delta y \sum_{j=1}^{q \cdot l/L_{2n}} \frac{1 - \exp(-j)}{j} \cdot \frac{l}{L_{2n}} = \frac{\delta y \cdot l}{L_{2n}} \ln(q+1) = \frac{l}{2} \tan \theta \ln(q+1). \quad (34)$$

20

$$D(y_a) = \frac{l}{2} \cdot \ln\left(\frac{2y_a}{l \tan \theta} + 1\right) \tan \theta. \quad (35)$$

Naturally, $D(y_a) \rightarrow y_a$, $y_a \rightarrow 0$.

25 Transmission and averaged transmission as a function of physical lens aperture described by the dimension-less parameter q is illustrated in Fig. 7. This pertains only to the special case $y=1$.

Assume in the following $q=10$. Perhaps it is more useful to see how D depends on F .
After some algebra we get

$$D = 2\delta\sqrt{F/\lambda}. \quad (36)$$

5 Then, the gain is ($F \ll s_0$):

$$G = 0.94 \cdot \frac{s_p D}{d_o F}. \quad (37)$$

The refractive element and the lens according to the invention can be fabricated in various ways. According to a preferred embodiment, it is possible to form these
10 structures by standard lithographic patterning and subsequent deep-etching in silicon. These lenses can then be used as moulds for chemical vapor deposition of diamond. For best performance, the angle θ should be as small as this process may allow.

The lens according to the preferred embodiment of the invention can be used in an x-ray
15 apparatus 86, as illustrated very schematically in Fig. 8, comprising an x-ray source, the lens 80 (combined refractive elements) and a detector assembly 87. Of course, the apparatus can comprise an array of refractive elements or lenses and the lenses can be arranged in a different position in the ray path. The detector assembly can be any of a film, a semiconductor detector, gaseous detector etc.

20

All calculations above pertain to using only one lens half, i.e. a refractive element. Of course, as for the MPL, two halves can be used to double the aperture and intensity. These lenses are focusing in one direction only. Two lenses can be used to form a point
25 focus if one is rotated, e.g. 90° around the optical axis. Fig. 9 illustrates two refractive elements 90a and 90b arranged displaced relative each other in series. Element 90a is to focus the rays 95 horizontally while the element 90b is arranged for vertical focusing.

The invention is not limited to the shown embodiments but can be varied in a number of ways without departing from the scope of the appended claims and the arrangement and
30 the method can be implemented in various ways depending on application, functional units, needs and requirements etc.

CLAIMS

Huvudfaxen Kus

1. A refractive element (10, 20), suitable for refracting x-rays, comprising a body of low-Z material having a first end adapted to receive rays emitted from a ray source and a second end from which the rays received at the first end emerge, characterised in that said refractive element comprises columns of stacked substantially identical prisms (21).
2. The element of claim 1, wherein said prisms are produced by removal of material corresponding to a multiple of a phase-shift length (L_{2n}) of a multiple of $2n$.
3. The element according to any of preceding claims, wherein an intensity transmission of the element is

$$T(y) = \exp(-X(y)/l) = \exp(-k|y|l)$$

wherein $X(y)$ is the total path length for a ray through the element, l is an attenuation length, k is constant and y is the distance to the optical axis.

4. The element according to any of preceding claims, wherein an effective aperture is defined by:

$$D = \frac{\delta F}{\tan \theta}$$

wherein F is the focal length, δ is the decrement of a real part of an index of refraction, l is an attenuation length and θ is the side angle of the prisms.

5. The element according to any of preceding claims, wherein an aperture increase factor (AIF) is defined by:

$$AIF = 3.2 \cdot \frac{\sigma_{abs}}{L_{2\pi} \tan \theta}$$

wherein σ_{abs} is root-mean-square width of MPL aperture, $L_{2\pi}$ is 2π -shift length, and θ is the side angle of the prisms.

6. The element according to any of preceding claims, comprising of one or several of Silicon or diamond.
- 5 7. The element according to any of preceding claims, wherein a focal length is controlled by a deviation length (y_0) of one end of the element with respect to the incident ray.
- 10 8. A lens (30), suitable for x-rays, comprising a body with low-Z material having a first end adapted to receive rays emitted from a ray source and a second end from which the rays received at the first end are refracted, characterised in that said lens comprises two columns of stacked substantially identical prisms (21) arranged in an angle relative each other.
- 15 9. The lens of claim 8, wherein said prisms are produced by removal of material corresponding to a multiple of a phase-shift length (L_{2n}) of a multiple of $2n$.
10. The lens of claim 8, wherein said columns are displaced relative each other.
- 20 11. The lens of claim 10, wherein said columns are rotated relative each other.
12. The lens of claim 10, wherein said columns are arranged in series.
- 25 13. An x-ray apparatus (86) comprising at least an x-ray source (87) and a detector assembly (88), further comprising a refractive element according to any of claims 1-7.
- 30 14. An x-ray apparatus (86) comprising at least an x-ray source (87) and a detector assembly (88), further comprising a lens (30) according to any of claims 8 to 12.

15

15. A method for fabricating an element according to any of claims 1-7, the method comprising: providing an element comprising prism-patterns by lithographic patterning and subsequent deep-etching in silicon.

5

16. The method of claim 15, further comprising using said element as moulds for chemical vapor deposition of diamond.

10

17. A method for reducing absorption in multi-prism lens, the method comprising removing material only resulting in a phase-shift of a multiple of 2π .



Ink. t. Patent- och reg

2003 -03- 2

Huvudfaxen Kass

Abstract

5 For reducing absorption in a refractive element, the present invention relates to a refractive element (10, 20), suitable for refracting x-rays, comprising a body with low-Z material having a first end adapted to receive rays emitted from a ray source and a second end from which the rays received at the first end emerge. The refractive element comprises columns of stacked substantially identical prisms (21).

10 (Fig. 2)

1/5

Ink. t. Patent- och reg.v

2003 -U3- 2 1

Huvudfoxen Kasec




Fig. 1a




Fig. 1b




Fig. 2

2/5




Fig. 3




Fig. 4




Fig. 5




Fig. 6a




Fig. 6b

Ink. t. Patent- och reg

2003-03-2

Huvudfaxen Ka:

4/5




Fig. 7




Fig. 8

Ink. t. Patent- och reg.verket

2003-03-21

Huvudfaxen Kossan




Fig. 9

This Page is inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☒ BLACK BORDERS

☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☒ FADED TEXT OR DRAWING

☒ BLURED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☐ COLORED OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☐ LINES OR MARKS ON ORIGINAL DOCUMENT

☐ REPERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images problems checked, please do not report the problems to the IFW Image Problem Mailbox